

abstract	abstrakt[ne]	Something which cannot be directly instantiated; the opposite of <i>concrete</i> .
abstract class	abstraktklass	A <i>class</i> that cannot be directly instantiated. Contrast: <i>concrete class</i> .
abstraction	abstraktsioon	The creation of a <i>view</i> or <i>model</i> that suppresses unnecessary details to focus on a specific set of details of interest The essential characteristics of an entity that distinguish it from all other kinds of entities. An abstraction defines a boundary relative to the perspective of the viewer.
acceptance	vastuvõtmine	An action by which the customer accepts ownership of software products as a partial or complete performance of a contract.
action	toiming	The specification of an executable statement that forms an abstraction of a computational procedure. An action typically results in a change in the state of the system, and can be realized by sending a message to an object or modifying a link or a value of an attribute.
action sequence	toimingujada	An expression that resolves to a sequence of actions.
action state	toimingu olek	A state that represents the execution of an atomic action, typically the invocation of an <i>operation</i> .
activation	aktiveerimine	The execution of an <i>action</i> .
active class	aktiivne klass	A <i>class</i> representing a thread of control in the system. A class whose instances are active objects. See: active object.
activity	tegevus	A unit of work a <i>worker</i> may be asked to perform
active object	aktiivne objekt	An <i>object</i> that owns a <i>thread</i> and can initiate control activity. An instance of <i>active class</i> . See: <i>active class, thread</i> .
activity graph	tegevusskeem	A special case of a <i>state machine</i> that is used to model processes involving one or more classifiers. Contrast: <i>statechart diagram</i> . Synonym: <i>activity diagram</i> .
actor (instance)	tegija(isend)	Someone or something, outside the system or business that interacts with the system or business.
actor class	tegijaklass	Defines a set of actor instances, in which each actor instance plays the same role in relation to the system or business. A coherent set of roles that users of use cases play when interacting with these use cases. An actor has one role for each <i>use case</i> with which it communicates.
actor-generalization	tegija üldistus	An actor-generalization from an actor class (descendant) to another actor class (ancestor) indicates that the descendant inherits the role the ancestor can play in a use case.
actual parameter	tegelik parameeter	Synonym: <i>argument</i> .
aggregate [class]	agregaat	A class that represents the "whole" in an aggregation (whole-part) relationship. See: <i>aggregation</i> .
aggregation	agregatsioon	An association that models a whole-part relationship between an aggregate (the whole) and its parts. A special form of association that specifies a whole-part relationship between the aggregate (whole) and a component part. See: <i>composition</i> .
analysis	analüüs	The part of the software development process

analysis class	analüüsiklass	<p>whose primary purpose is to formulate a model of the problem <i>domain</i>. Analysis focuses on what to do, design focuses on how to do it. See <i>design</i>.</p> <p>An abstraction of a <i>role</i> played by a design element in the system, typically within the context of a <i>use-case realization</i>. Analysis classes may provide an abstraction for several role, representing the common behavior of those roles. Analysis classes typically evolve into one or more design elements (e.g. design <i>classes</i> and/or <i>capsules</i>, or design <i>subsystems</i>).</p>
analysis & design	analüüs ja projekteerimine	<p>A <i>core workflow</i> in the Unified Process, whose purpose is to show how the system's <i>use cases</i> will be realized in implementation; (general) activities during which strategic and tactical decisions are made to meet the required functional and quality <i>requirements</i> of a system. For the result of analysis and design activities, see "<i>Design Model</i>."</p>
analysis mechanism	analüüsimehhanism	<p>An architectural mechanism used early in the <i>design</i> process, during the period of discovery when key <i>classes</i> and <i>subsystems</i> are being identified. Typically analysis mechanisms capture the key aspects of a solution in a way that is implementation independent. Analysis mechanisms are usually unrelated to the problem domain, but instead are "computer science" concepts. They provide specific behaviors to a domain-related <i>class</i> or <i>component</i>, or correspond to the implementation of cooperation between classes and/or components. They may be implemented as a <i>framework</i>. Examples include mechanisms to handle persistence, inter-process communication, error or fault handling, notification, and messaging, to name a few.</p>
analysis time	analüüsiaeg	<p>Refers to something that occurs during an analysis phase of the software development process. See: <i>design time</i>, <i>modeling time</i>.</p>
architectural baseline	arhitektuuri arendusalus	<p>The <i>baseline</i> at the end of the <i>Elaboration</i> phase, at which time the foundation structure and behavior of the system is stabilized.</p>
architectural mechanism	arhitektuurimehhanism	<p>An architectural mechanism represents a common solution to a frequently encountered problem. They may be patterns of structure, patterns of behavior, or both.</p>
architectural pattern	arhitektuurimall	<p>A description of an archetypal solution to a recurrent design problem that reflects well-proven design experience. Presented in the Software Architecture Document.</p>
architectural view	arhitektuurivaade	<p>A view of the system <i>architecture</i> from a given perspective; focuses primarily on structure, modularity, essential components, and the main control flows.</p>
architecture	arhitektuur	<p>The highest level concept of a system in its environment [<i>IEEE</i>]. The architecture of a software system (at a given point in time) is its organization or structure of significant <i>components</i> interacting through <i>interfaces</i>, those components being composed of</p>

		successively smaller components and interfaces. The organizational structure of a system. An architecture can be recursively decomposed into parts that interact through interfaces, relationships that connect parts, and constraints for assembling parts. Parts that interact through interfaces include <i>classes</i> , <i>components</i> and <i>subsystems</i> .
argument	argument	A binding for a parameter that resolves to a run-time instance. Synonym: <i>actual parameter</i> . Contrast: <i>parameter</i> .
artifact	tehis	(1) A piece of information that (1) is produced, modified, or used by a process, (2) defines an area of responsibility, and (3) is subject to version control. An artifact can be a <i>model</i> , a <i>model element</i> , or a <i>document</i> . A document can enclose other documents. A piece of information that is used or produced by a software development process. An artifact can be a model, a description, or software. Synonym: <i>product</i> .
artifact guidelines	tehisejuhised	A description of how to work with a particular <i>artifact</i> , including how to create and revise the artifact.
artifact set	tehistik	A set of related artifacts which presents one aspects of the system. Artifact sets cut across <i>core workflows</i> , as several artifacts are used in a number of core workflows (e.g. the Risk List, the Software Architecture Document, and the Iteration Plan).
association	side	A relationship that models a bi-directional semantic connection among instances. The semantic relationship between two or more classifiers that specifies connections among their instances.
association class	sidemeklass	A model element that has both <i>association</i> and <i>class</i> properties. An association class can be seen as an association that also has class properties, or as a class that also has association properties.
association end	sidemeots	The endpoint of an association, which connects the association to a <i>classifier</i> .
asynchronous action	asünkroonne toiming	A request where the sending object does not pause to wait for results. Contrast: <i>synchronous action</i> .
attribute	atribuut	An attribute defined by a <i>class</i> represents a named property of the class or its objects. An attribute has a <i>type</i> that defines the type of its instances. A feature within a classifier that describes a range of values that instances of the classifier may hold.
baseline	arendusalus	A reviewed and approved release of <i>artifacts</i> that constitutes an agreed basis for further evolution or development and that can be changed only through a formal procedure, such as <i>change management</i> and <i>configuration control</i> .
behavior	käitumine	The observable effects of an operation or event, including its results.
behavioral feature	käitumisjoon	A dynamic feature of a <i>model element</i> , such as an <i>operation</i> or <i>method</i> .
behavioral model aspect	modeli käitumisaspekt	A <i>model aspect</i> that emphasizes the behavior of the <i>instances</i> in a system, including their

binary association	kahendassotsiatsioon	<i>methods, collaborations, and state histories.</i>
binding	sidumine	An association between two <i>classes</i> . A special case of an <i>n-ary association</i> .
boolean	Boole'i muutuja	The creation of a <i>model element</i> from a <i>template</i> by supplying arguments for the parameters of the template.
boolean expression	Boole'i avaldis	An enumeration whose values are true and false.
boundary class	piiriklass	An expression that evaluates to a <i>boolean</i> value.
build	redaktsioon	A class used to model communication between the system's environments and its inner workings.
call	kutse	An operational version of a system or part of a system that demonstrates a subset of the capabilities to be provided in the final product.
capsule	kapsel	An <i>action state</i> that invokes an <i>operation</i> on a <i>classifier</i> .
cardinality	võimsus	A specific <i>design pattern</i> which represents an encapsulated <i>thread</i> of control in the system. A capsule is a <i>stereotyped class</i> with a specific set of required and restricted <i>associations</i> and <i>properties</i> .
change control board (CCB)	muutmismõukogu	The number of elements in a set. Contrast: <i>multiplicity</i> .
child	tütar	The role of the CCB is to provide a central control mechanism to ensure that every <i>change request</i> is properly considered, authorized and coordinated.
change management	muutusehaldus	In a <i>generalization</i> relationship, the specialization of another element, the parent. See: <i>subclass, subtype</i> . Contrast: <i>parent</i> .
change request (CR)	muutmistaotlus	The activity of controlling and tracking changes to <i>artifacts</i> . See also: <i>scope management</i> .
checkpoints	kontrolltingimused	A general term for any request from a <i>stakeholder</i> to change an <i>artifact</i> or <i>process</i> . Documented in the Change Request is information on the origin and impact of the current problem, the proposed solution, and its cost. See also: <i>enhancement request, defect</i> .
class	klass	A set of conditions that well-formed <i>artifacts</i> of a particular type should exhibit. May also be stated in the form of questions which should be answered in the affirmative.
class diagram	klassiskeem	A description of a set of objects that share the same <i>attributes, operations, methods, relationships, and semantics</i> . A class may use a set of interfaces to specify collections of operations it provides to its environment. See: <i>interface</i> .
client	klient	A diagram that shows a collection of declarative (static) <i>model elements</i> , such as <i>classes, types, and their contents and relationships</i> .
classifier	klassifikaator	A <i>classifier</i> that requests a service from another classifier. Contrast: <i>supplier</i> .
collaboration	koostöö	A mechanism that describes behavioral and structural features. Classifiers include <i>interfaces, classes, datatypes, and components</i> .
		(1) Is a description of a collection of objects that interact to implement some behavior

within a context. It describes a society of cooperating objects assembled to carry out some purpose. (2) It captures a more holistic view of behavior in the exchange of messages within a network of objects. (3) Collaborations show the unity of the three major structures underlying computation: data structure, control flow, and data flow. (4) A collaboration has a static and a dynamic part. The static part describes the roles that objects and links play in an instantiation of the collaboration. The dynamic part consists of one or more dynamic interactions that show message flow over time in the collaboration to perform computations. A collaboration may have a set of *messages* to describe its dynamic behavior. (5) A collaboration with messages is an interaction. The specification of how an *operation* or *classifier*, such as a *use case*, is realized by a set of classifiers and *associations* playing specific roles used in a specific way. The collaboration defines an interaction. See: *interaction*.

collaboration diagram **koostööskeem**

(1) A collaboration diagram describes a pattern of interaction among objects; it shows the objects participating in the interaction by their links to each other and the *messages* they send to each other. (2) It is a *class diagram* that contains *classifier* roles and *association* roles rather than just classifiers and associations. (3) Collaboration diagrams and sequence diagrams both show interactions, but they emphasize different aspects. Sequence diagrams show time sequences clearly but do not show object relationships explicitly. Collaboration diagrams show object relationships clearly, but time sequences must be obtained from sequence numbers. A diagram that shows interactions organized around the structure of a *model*, using either classifiers and associations or instances and links. Unlike a sequence diagram, a collaboration diagram shows the relationships among the instances. Sequence diagrams and collaboration diagrams express similar information, but show it in different ways. See: *sequence diagram*.

comment **kommentaar**

An annotation attached to an element or a collection of elements. A note has no semantics. Contrast: *constraint*.

communicates-association **kasutusside**

An association between an *actor class* and a *use case class*, indicating that their instances interact. The direction of the association indicates the initiator of the communication (Unified Process convention).

communication association **suhtlusside**

In a deployment diagram an association between nodes that implies a communication. See: *deployment diagram*.

compile time **kompileerimisaegne**

Refers to something that occurs during the compilation of a software module. See: *modeling time*, *run time*.

component **komponent**

A non-trivial, nearly independent, and replaceable part of a system that fulfills a clear

		function in the context of a well-defined <i>architecture</i> . A component conforms to and provides the physical realization of a set of <i>interfaces</i> . A physical, replaceable part of a system that packages implementation and conforms to and provides the realization of a set of interfaces. A component represents a physical piece of implementation of a system, including software code (source, binary or executable) or equivalents such as scripts or command files.
component diagram	komponendiskeem	A diagram that shows the organizations and dependencies among <i>components</i> .
component-based development (CBD)	komponendipõhine arendus	The creation and deployment of software-intensive systems assembled from <i>components</i> as well as the development and harvesting of such components.
component subsystem	komponentalamsüsteem	A <i>stereotyped</i> subsystem (i.e. «component») representing the logical abstraction in design of a <i>component</i> . It realizes one or more <i>interfaces</i> , and may be dependent on one or more interfaces. It may enclose zero or more <i>classes</i> , <i>packages</i> or other component subsystems, none of which are visible externally (only interfaces are visible). It may also enclose zero or more diagrams which illustrate internal behavior (e.g. <i>state</i> , <i>sequence</i> or <i>collaboration diagrams</i>).
composite [class]	liitklass	A <i>class</i> that is related to one or more classes by a composition relationship. See: <i>composition</i> .
composite aggregation	liitside	Synonym: <i>composition</i> .
composite state	liitolek	A state that consists of either concurrent (orthogonal) substates or sequential (disjoint) substates. See: <i>substate</i> .
composite substate	liit-alamolek	A <i>substate</i> that can be held simultaneously with other substates contained in the same composite state. Synonym: <i>region</i> . See: <i>composite state</i> .
composition	kompositsioon	A form of <i>aggregation</i> association with strong ownership and coincident lifetime as part of the whole. Parts with non-fixed <i>multiplicity</i> may be created after the <i>composite</i> itself, but once created they live and die with it (i.e., they share lifetimes). Such parts can also be explicitly removed before the death of the composite. Composition may be recursive. Synonym: <i>composite aggregation</i> .
concrete	konkreet[ne]	An entity in a configuration that satisfies an end-use function and can be uniquely identified at a given reference point. (<i>ISO</i>)
concrete class	konkreetklass	A <i>class</i> that can be directly instantiated. Contrast: <i>abstract class</i> .
concurrency	konkurrentsus	The occurrence of two or more activities during the same time interval. Concurrency can be achieved by interleaving or simultaneously executing two or more threads. See: <i>thread</i> .
concurrent substate	konkurrentne alamolek	A <i>substate</i> that can be held simultaneously with other substates contained in the same composite state. See: <i>composite substate</i> . Contrast: <i>disjoint substate</i> .

configuration	konfiguratsioon	(1) general: The arrangement of a system or network as defined by the nature, number, and chief characteristics of its functional units; applies to both hardware or software configuration. (2) The requirements, design, and implementation that define a particular version of a system or system component. See <i>configuration management</i> .
configuration item	konfiguratsioonielement	An entity in a configuration that satisfies an end-use function and can be uniquely identified at a given reference point. (ISO)
configuration management	konfiguratsioonihaldus	A supporting process whose purpose is to identify, define, and baseline items; control modifications and releases of these items; report and record status of the items and modification requests; ensure completeness, consistency and correctness of the items; and control storage, handling and delivery of the items. (ISO)
control class	kontrollklass	A <i>class</i> used to model behavior specific to one, or a several <i>use cases</i> .
constraint	kitsendus	A semantic condition or restriction. Certain constraints are predefined in the UML, others may be user defined. Constraints are one of three extensibility mechanisms in UML. See: <i>tagged value, stereotype</i> .
construction	konstrueerimine	The third phase of the Unified Process, in which the software is brought from an executable architectural baseline to the point at which it is ready to be transitioned to the user community.
container	konteiner	1. An <i>instance</i> that exists to contain other instances, and that provides operations to access or iterate over its contents. (for example, arrays, lists, sets). 2. A <i>component</i> that exists to contain other components.
containment hierarchy	sisalduvushierarhia	A namespace hierarchy consisting of <i>model elements</i> , and the containment relationships that exist between them. A containment hierarchy forms an acyclic graph.
context	kontekst	A view of a set of related <i>modeling elements</i> for a particular purpose, such as specifying an <i>operation</i> .
core workflow	põhivoog	One of nine core workflows in the Rational Unified Process: Business Modeling, Requirements, Analysis & Design, Implementation, Test, Deployment, Configuration & Change Management, Project Management, Environment. An abstract business use case of the Software-Engineering Business.
critical design review (CDR)	lahenduse kriitiline läbivaatus	In the waterfall life-cycle, the major review held when the detailed design is completed (see Guidelines: Project Plan).
customer	tellija	A person or organization, internal or external to the producing organization, who takes financial responsibility for the system. In a large system this may not be the end user. The customer is the ultimate recipient of the developed product and its artifacts. See also: <i>stakeholder</i> .
cycle	tsükkel	One complete pass through the four phases: <i>inception, elaboration, construction</i> and

datatype	andmetüüp	<p><i>transition</i>. The span of time between the beginning of the inception phase and the end of the transition phase.</p> <p>A descriptor of a set of values that lack identity and whose operations do not have side effects. Datatypes include primitive pre-defined types and user-definable types. Pre-defined types include numbers, string and time. User-definable types include enumerations.</p>
deadlock	tupik	<p>A condition in which two independent threads of control are blocked, each waiting for the other to take some action. Deadlock often arises from adding synchronization mechanisms to avoid <i>race conditions</i>.</p>
defect	defekt	<p>An anomaly, or flaw, in a delivered work product. Examples include such things as omissions and imperfections found during early lifecycle phases and symptoms of faults contained in software sufficiently mature for test or operation. A defect can be any kind of issue you want tracked and resolved. See also: <i>change request</i>.</p>
defining model [MOF]	defineeriv mudel	<p>The model on which a repository is based. Any number of repositories can have the same defining model.</p>
delegation	delegerimine	<p>The ability of an object to issue a <i>message</i> to another object in response to a message. Delegation can be used as an alternative to inheritance. Contrast: <i>inheritance</i>.</p>
deliverable	saadus	<p>An output from a process that has a value, material or otherwise, to a <i>customer</i> or other <i>stakeholder</i>.</p>
dependency	sõltuvus	<p>A relationship between two <i>modeling elements</i>, in which a change to one modeling element (the independent element) will affect the other modeling element (the dependent element).</p>
deployment	evitus	<p>A <i>core process workflow</i> in the software-engineering process, whose purpose is to ensure a successful transition of the developed system to its users. Included are <i>artifacts</i> such as training materials and installation procedures.</p>
deployment diagram	evituskeem	<p>A diagram that shows the configuration of run-time processing nodes and the <i>components, processes, and objects</i> that live on them. Components represent run-time manifestations of code units. See: <i>component diagram</i>.</p>
deployment view	evitusvaade	<p>An <i>architectural view</i> that describes one or several system configurations; the mapping of software <i>components</i> (tasks, modules) to the computing nodes in these configurations.</p>
derived element	tuletiselement	<p>A model element that can be computed from another element, but that is shown for clarity or that is included for design purposes even though it adds no semantic information.</p>
design	projekteerimine	<p>The part of the software development process whose primary purpose is to decide how the system will be implemented. During design, strategic and tactical decisions are made to meet the required functional and quality</p>

design time	projekteerimisaegne	<i>requirements</i> of a system. See <i>analysis</i> . Refers to something that occurs during a design phase of the software development process. See: <i>modeling time</i> . Contrast: <i>analysis time</i> .
design mechanism	projekteerimismehhanism	An <i>architectural mechanism</i> used during the design process, during the period in which the details of the design are being worked-out. They are related to associated <i>analysis mechanisms</i> , of which they are additional refinements. A design mechanism assumes some details of the implementation environment, but it is not tied to a specific implementation (as is an <i>implementation mechanism</i>). For example, the analysis mechanism for inter-process communication may be refined by several design mechanisms for interprocess communication (IPC): shared memory, function-call-like IPC, semaphore-based IPC, and so on. Each design mechanism has certain strengths and weaknesses; the choice of a particular design mechanism is determined by the characteristics of the objects using the mechanism.
design model	projekteerimismudel	An <i>object model</i> describing the realization of <i>use cases</i> ; serves as an abstraction of the <i>implementation model</i> and its source code.
design package	projekteerimispakett	A collection of <i>classes</i> , <i>relationships</i> , <i>use-case realizations</i> , <i>diagrams</i> , and other <i>packages</i> ; it is used to structure the <i>design model</i> by dividing it into smaller parts.
design pattern	projekteerimismall	A specific solution to a particular problem in software design. Design patterns capture solutions that have developed and evolved over time, expressed in a succinct and easily applied form. Generally design patterns express solutions at a lower level of granularity than mechanisms, and may very well be used to design a <i>design mechanism</i> .
design subsystem	projekteerimis-alamsüsteem	A <i>design package</i> that contains a collection of design packages and <i>classes</i> , and used to structure the <i>design model</i> by dividing it into smaller parts. See: <i>design package</i> .
developer	väljatöötaja	A person responsible for developing the required functionality in accordance with project-adopted standards and procedures. This can include performing activities in any of the requirements, analysis & design, implementation, and test workflows.
development case	väljatöötusjuhtum	The software-engineering process used by the performing organization. It is developed as a configuration, or customization, of the Unified Process product, and adapted to the project's needs.
development process	väljatööteprotsess	A set of partially ordered steps performed for a given purpose during software development, such as constructing models or implementing models.
device	vahend	A type of <i>node</i> which provides supporting capabilities to a <i>processor</i> . Although it may be capable of running embedded programs (device drivers), it cannot execute general-purpose applications, but instead exists only to

		serve a processor running general-purpose applications.
diagram	skeem	A graphical depiction of all or part of a <i>model</i> . A graphical presentation of a collection of <i>model elements</i> , most often rendered as a connected graph of arcs (relationships) and vertices (other model elements). UML supports the following diagrams: <i>class diagram</i> , <i>object diagram</i> , <i>use-case diagram</i> , <i>sequence diagram</i> , <i>collaboration diagram</i> , <i>statechart diagram</i> , <i>activity diagram</i> , <i>component diagram</i> , and <i>deployment diagram</i> .
disjoint substate	ird-alamolek	A <i>substate</i> that cannot be held simultaneously with other substates contained in the same composite state. See: <i>composite state</i> . Contrast: <i>concurrent substate</i> .
distribution unit	jaotusiüksus	A set of <i>objects</i> or <i>components</i> that are allocated to a process or a processor as a group. A distribution unit can be represented by a run-time <i>composite</i> or an <i>aggregate</i> .
document	dokument	A document is a collection of information that is intended to be represented on paper, or in a medium using a paper metaphor. The paper metaphor includes the concept of pages, and it has either an implicit or explicit sequence of contents. The information is in text or two-dimensional pictures. Examples of paper metaphors are word processor documents, spreadsheets, schedules, Gantt charts, web-pages, or overhead slide presentations.
document description	dokumendi kirjeldus	Describes the contents of a particular document.
document template	dokumendimall	A concrete tool template, such as a Adobe® FrameMaker™ or Microsoft® Word™ template.
domain	valdkond	An area of knowledge or activity characterized by a family of related systems. An area of knowledge or activity characterized by a set of concepts and terminology understood by practitioners in that area.
domain model	valdkonnamudel	A domain model captures the most important types of objects in the context of the <i>domain</i> . The domain objects represent the entities that exist or events that transpire in the environment in which the system works. The domain model is a subset of the business object model.
dynamic classification	dünaamiline liigitus	A semantic variation of <i>generalization</i> in which an <i>object</i> may change <i>type</i> or <i>role</i> . Contrast: <i>static classification</i> .
elaboration	detailimine	The second <i>phase</i> of the process where the product <i>vision</i> and its <i>architecture</i> are defined.
element enclosed document	element manuskument	An atomic constituent of a <i>model</i> . A <i>document</i> can be enclosed by another document to collect a set of documents into a whole; the enclosing document as well as the individual enclosures are regarded as separate <i>artifacts</i> .
enhancement request	täiendustaotlus	A type of <i>stakeholder request</i> that specifies a new <i>feature</i> or functionality of the system. See also: <i>change request</i>
entity class	olemiklass	A <i>class</i> used to model information that has

entry action	sisenemistoiming	been stored by the system, and the associated behavior. A generic class, reused in many <i>use cases</i> , often with persistent characteristics. An entity class defines a set of entity objects, which participate in several use cases and typically survive those use cases. An action executed upon entering a <i>state</i> in a <i>state machine</i> regardless of the transition taken to reach that state.
enumeration	väärtustik	A list of named values used as the range of a particular <i>attribute</i> type. For example, RGBColor = {red, green, blue}. Boolean is a predefined enumeration with values from the set {false, true}.
event	sündmus	The specification of a significant occurrence that has a location in time and space. In the context of <i>state diagrams</i> , an event is an occurrence that can trigger a <i>transition</i> .
environment	keskkond	A <i>core supporting workflow</i> in the software-engineering process, whose purpose is to define and manage the environment in which the system is being developed. Includes process descriptions, <i>configuration management</i> , and development tools.
evolution	areng	The life of the software after its initial development cycle; any subsequent cycle, during which the product evolves.
evolutionary	arenguline	An iterative development strategy that acknowledges that user needs are not fully understood and therefore requirements are refined in each succeeding iteration (<i>elaboration phase</i>).
exit action	väljumistoiming	An action executed upon exiting a <i>state</i> in a <i>state machine</i> regardless of the transition taken to exit that state.
export	eksport	In the context of <i>packages</i> , to make an element visible outside its enclosing namespace. See: <i>visibility</i> . Contrast: <i>export</i> [OMA], <i>import</i> .
expression	avaldis	A string that evaluates to a value of a particular type. For example, the expression "(7 + 5 * 3)" evaluates to a value of type number.
extend	laiendus	A relationship from an extension use case to a base use case, specifying how the behavior defined for the extension use case can be inserted into the behavior defined for the base use case.
extend-relationship	laiendusseos	An extend-relationship from a use-case class A to a use-case class B indicates that an instance of B may include (subject to specific conditions specified in the extension) the behavior specified by A. Behavior specified by several extenders of a single target use case can occur within a single use-case instance.
facade	fassaad	A special package, stereotyped «facade», within a subsystem that organizes and exports all information needed by the clients of the subsystem. Included in this package are <i>interfaces</i> (where the interfaces are unique to the subsystem), realization relationships to interfaces outside the subsystem, and any documentation needed by clients of the

fault	viga	subsystem to use the subsystem. An accidental condition that causes a component in the implementation model to fail to perform its required behavior. A fault is the root cause of one or more <i>defects</i> .	
feature	erisus	An externally observable service provided by the system which directly fulfills a <i>stakeholder need</i> . A property, like operation or attribute, which is encapsulated within a classifier, such as an interface, a class, or a datatype.	
final state	lõppolek	A special kind of state signifying that the enclosing <i>composite state</i> or the entire <i>state machine</i> is completed.	
fire	vallandama	To execute a state transition. See: <i>transition</i> .	
focus of control	juhtimiskese	A symbol on a <i>sequence diagram</i> that shows the period of time during which an object is performing an action, either directly or through a subordinate procedure.	
formal parameter framework	formaalparameeter	Synonym: <i>parameter</i> .	
	raamstruktuur	A micro- <i>architecture</i> that provides an extensible <i>template</i> for applications within a specific <i>domain</i> .	
FURPS	FURPS	An acronym representing categories for assessing product quality: Functionality, Usability, Reliability, Performance, Supportability. (funktsionaalsus, kasutuskõlblikkus, töökindlus, suutvus, toetatavus)	
generalizable element	üldistuv element	A model element that may participate in a generalization relationship. See: <i>generalization</i> .	
generalization	üldistus	A taxonomic relationship between a more general element and a more specific element. The more specific element is fully consistent with the more general element and contains additional information. An instance of the more specific element may be used where the more general element is allowed. See: <i>inheritance</i> .	
generation	põlv	Final release at the end of a cycle.	JOKA: valmistoode . "Põlv" ei haaku ju kuidagi sellega, mida see kolmandas veerus olev inglise keelne tekst räägib. Ega see inglisekeelne termin kah targem ei ole – generation on minuarust rohkem nigu põlvkond või nii. Ma ei imesta, kui see mingi viga seal RUP'is on.
green-field development	täisväljatootus	Development "starting from scratch", as opposed to "evolution of an existing system" or "reengineering of a legacy piece". (Originated from the transformation that takes place when building a new factory on an undeveloped site - with grass on it.)	
guard condition	siirdetingimus	A condition that must be satisfied in order to enable an associated <i>transition</i> to <i>fire</i> .	

IEEE	IEEE	The Institute of Electrical and Electronics Engineers, Inc.
ISO	ISO	The International Organization for Standardization.
implementation	teostus	A core process workflow in the software-engineering process, whose purpose is to implement and unit test the classes. A definition of how something is constructed or computed. For example, a class is an implementation of a type, a method is an implementation of an operation.
implementation inheritance	teostuspärilus	The inheritance of the implementation of a more specific element. Includes inheritance of the interface. Contrast: <i>interface inheritance</i> .
implementation mechanism	teostusmehhanism	An <i>architectural mechanism</i> used during the implementation process. They are refinements of <i>design mechanisms</i> , and specify the exact implementation of the mechanism. For example, one particular implementation of the inter-process communication analysis mechanism is a shared memory design mechanism utilizing a particular operating system's shared memory function calls. Concurrency conflicts (inappropriate simultaneous access to shared memory) may be prevented using semaphores, or using a latching mechanism, which in turn rest upon other implementation mechanisms.
implementation model	teostusmudel	The implementation model is a collection of <i>components</i> , and the <i>implementation subsystems</i> that contain them.
implementation subsystem	teostusalamsüsteem	A collection of <i>components</i> and other implementation subsystems, and is used to structure the <i>implementation model</i> by dividing it into smaller parts.
implementation view	teostusvaade	An <i>architectural view</i> that describes the organization of the static software elements (code, data, and other accompanying artifacts) on the development environment, in terms of both <i>packaging</i> , <i>layering</i> , and <i>configuration management</i> (ownership, release strategy, and so on). In the Unified Process it is a view on the implementation model.
import	import	In the context of <i>packages</i> , a dependency that shows the packages whose <i>classes</i> may be referenced within a given package (including packages recursively embedded within it). Contrast: <i>export</i> .
import-dependency	impordisõltuvus	A <i>stereotyped</i> dependency in the design whose source is a <i>design package</i> , and whose target is a different design package. The import dependency causes the public contents of the target package to be referenceable in the source package.
inception	algamine	The first <i>phase</i> of the Unified Process, in which the seed idea, request for proposal, for the previous generation is brought to the point of being (at least internally) funded to enter the <i>elaboration</i> phase.
include	sisalduvus	A relationship from a base use case to an inclusion use case, specifying how the behavior defined for the inclusion use case can be inserted into the behavior defined for the

include-relationship	sisalduvusseos	base use case. An include-relationship is a relationship from a base use case to an inclusion use case, specifying how the behavior defined for the inclusion use case is explicitly inserted into the behavior defined for the base use case.
increment	inkrement	The difference (<i>delta</i>) between two releases at the end of subsequent <i>iterations</i> .
incremental	inkrementaalne	Qualifies an iterative development strategy in which the system is built by adding more and more functionality at each <i>iteration</i> .
inheritance	pärilus	The mechanism that makes generalization possible; a mechanism for creating full class descriptions out of individual class segments. The mechanism by which more specific elements incorporate structure and behavior of more general elements related by behavior. See <i>generalization</i> .
input	sisendtehis	An <i>artifact</i> used by a process. See static artifact.
inspection	inspekterimine	A formal evaluation technique in which some <i>artifact</i> (model, document, software) is examined by a person or group other than the originator, to detect faults, violations of development standards, and other problems.
instance	isend	An individual entity satisfying the description of a <i>class</i> or <i>type</i> . An entity to which a set of operations can be applied and which has a state that stores the effects of the operations. See: <i>object</i> .
integration	integratsioon	The software development activity in which separate software components are combined into an executable whole.
integration build plan	integratsiooni järguplaan	Defines the order in which components are to be implemented and integrated in a specific iteration. Enclosed in the Iteration Plan.
interaction	interaktsioon	A specification of how stimuli are sent between <i>instances</i> to perform a specific task. The interaction is defined in the context of a collaboration. See <i>collaboration</i> .
interaction diagram	interaktsiooniskeem	A generic term that applies to several types of diagrams that emphasize object interactions. These include: <i>collaboration diagrams</i> , <i>sequence diagrams</i> , and <i>activity diagrams</i> .
interface	liides	A collection of <i>operations</i> that are used to specify a service of a <i>class</i> or a <i>component</i> . A named set of operations that characterize the behavior of an element.
interface inheritance	liidesepärilus	The inheritance of the interface of a more specific element. Does not include inheritance of the implementation. Contrast: <i>implementation inheritance</i> .
internal transition	sisesiire	A <i>transition</i> signifying a response to an event without changing the <i>state</i> of an object.
iteration	iteratsioon	A distinct sequence of activities with a base-lined plan and valuation criteria resulting in a <i>release</i> (internal or external).
key mechanism	võtmehhanism	A description of how an <i>architectural patterns</i> is realized in terms of patterns of interaction between elements in the system. Presented in the Software Architecture Document
layer	kiht	A specific way of grouping <i>packages</i> in a model at the same level of abstraction. The

		organization of classifiers or packages at the same level of abstraction. A layer represents a horizontal slice through an architecture, whereas a partition represents a vertical slice. Contrast: <i>partition</i> .	
link	link	A semantic connection among a tuple of objects. An instance of an association. See: <i>association</i> .	
link end	lingiots	An instance of an association end. See: <i>association end</i> .	
logical view	loogikavaade	An <i>architectural view</i> that describes the main classes in the design of the system: major business-related classes, and the classes that define key behavioral and structural mechanisms (persistency, communications, fault-tolerance, user-interface). In the Unified Process, the logical view is a <i>view</i> of the <i>design model</i> .	
management	haldus	A <i>core supporting workflow</i> in the software-engineering process, whose purpose is to plan and manage the development project.	
message	teade	A specification of the conveyance of information from one instance to another, with the expectation that activity will ensue. A message may specify the raising of a signal or the call of an operation.	
metaclass	metaklass	A class whose instances are classes. Metaclasses are typically used to construct <i>metamodels</i> .	
meta-metamodel	meta-metamudel	A model that defines the language for expressing a <i>metamodel</i> . The relationship between a meta-metamodel and a metamodel is analogous to the relationship between a metamodel and a <i>model</i> .	
metamodel	metamudel	A model that defines the language for expressing a <i>model</i> .	
metaobject	metaobjekt	A generic term for all metaentities in a metamodeling language. For example, metatypes, metaclasses, metaattributes, and metaassociations.	
method	meetod	(1) A regular and systematic way of accomplishing something; the detailed, logically ordered plans or procedures followed to accomplish a task or attain a goal. (2) UML 1.1: The implementation of an operation, the algorithm or procedure that effects the results of an operation. The implementation of an operation. It specifies the algorithm or procedure associated with an operation.	
milestone	tähtpunkt	The point at which an iteration formally ends; corresponds to a <i>release</i> point.	JOKA: verstapost?
model [MOF]	mudel	A semantically closed abstraction of a system. In the Unified Process, a complete description of a system from a particular perspective ('complete' meaning you don't need any additional information to understand the system from that perspective); a set of model elements. Two models cannot overlap. A semantically closed abstraction of a subject system. See: <i>system</i> . Usage note: In the context of the MOF specification, which describes a <i>meta-metamodel</i> , for brevity the meta-metamodel is frequently referred to as	

model aspect	mudeli aspekt	<p>simply the model.</p> <p>A dimension of modeling that emphasizes particular qualities of the <i>metamodel</i>. For example, the structural model aspect emphasizes the structural qualities of the metamodel.</p>
model elaboration	mudeli detailimine	<p>The process of generating a <i>repository</i> type from a published model. Includes the generation of interfaces and implementations which allows repositories to be instantiated and populated based on, and in compliance with, the model elaborated.</p>
model element [MOF]	mudeli element	<p>An element that is an abstraction drawn from the system being modeled. Contrast: <i>view element</i>. In the MOF specification model elements are considered to be <i>metaobjects</i>.</p>
modeling conventions	modelleerimisreeglid	<p>How concepts will be represented, restrictions on the modeling language that the project team management has decided upon (i.e. dictums such as "Do not use inheritance between subsystems."; "Do not use extend or include associations in the Use Case Model."; "Do not use the friend construct in C++."). Presented in the Software Architecture Document.</p>
modeling time	modelleerimisaegne	<p>Refers to something that occurs during a modeling phase of the software development process. It includes analysis time and design time. Usage note: When discussing object systems, it is often important to distinguish between modeling-time and run-time concerns. See: <i>analysis time, design time</i>. Contrast: <i>run time</i>.</p>
module	moodul	<p>A software unit of storage and manipulation. Modules include source code modules, binary code modules, and executable code modules. See: <i>component</i>.</p>
multiple classification	mitmene liigitus	<p>A semantic variation of <i>generalization</i> in which an object may belong directly to more than one class. See: <i>dynamic classification</i>.</p>
multiple inheritance	mitmene pärilus	<p>A semantic variation of <i>generalization</i> in which a type may have more than one <i>supertype</i>. Contrast: <i>single inheritance</i>.</p>
multiplicity	võimsustik	<p>A specification of the range of allowable cardinalities that a set may assume. Multiplicity specifications may be given for roles within associations, parts within composites, repetitions, and other purposes. Essentially a multiplicity is a (possibly infinite) subset of the non-negative integers. Contrast: <i>cardinality</i>.</p>
multi-valued [MOF]	mitmeväärtuseline	<p>A model element with <i>multiplicity</i> defined whose Multiplicity Type::upper attribute is set to a number greater than one. The term multi-valued does not pertain to the number of values held by an attribute, parameter, etc. at any point in time. Contrast: <i>single-valued</i>.</p>
n-ary association	n-ndassotsiatsioon	<p>An association among three or more classes. Each instance of the association is an n-tuple of values from the respective classes. Contrast: <i>binary association</i>.</p>
name namespace	nimi nimeruum	<p>A string used to identify a <i>model element</i>. A part of the model in which the names may</p>

node	sõlm	be defined and used. Within a namespace, each name has a unique meaning. See: <i>name</i> . A node is classifier that represents a run-time computational resource, which generally has at least a memory and often processing capability. Run-time objects and components may reside on nodes.
object	objekt	An entity with a well-defined boundary and identity that encapsulates <i>state</i> and <i>behavior</i> . State is represented by <i>attributes</i> and <i>relationships</i> , behavior is represented by <i>operations</i> , <i>methods</i> , and <i>state machines</i> . An object is an instance of a class. See: <i>class</i> , <i>instance</i> .
object diagram	objektiskeem	A diagram that encompasses <i>objects</i> and their relationships at a point in time. An object diagram may be considered a special case of a class diagram or a collaboration diagram. See: <i>class diagram</i> , <i>collaboration diagram</i> .
object flow state	objekti voo-olek	A <i>state</i> in an <i>activity graph</i> that represents the passing of an object from the output of actions in one state to the input of actions in another state.
object lifeline	objekti eluiga	A line in a sequence diagram that represents the existence of an object over a period of time. See: <i>sequence diagram</i> .
object model operation	objektmudel operatsioon	An abstraction of a system's implementation. A service that can be requested from an object to effect behavior. An operation has a <i>signature</i> , which may restrict the actual parameters that are possible.
operating system process	operatsioonisüsteemi protsess	An unique address space and execution environment in which instances of classes and subsystems reside and run. The execution environment may be divided into one or more threads of control. See also <i>process</i> and <i>thread</i> .
originator	lähetaja	An originator is anyone who submits a <i>change request</i> (CR). The standard change request mechanism requires the originator to provide information on the current problem, and a proposed solution in accordance with the change request form.
output	väljundtehis	Any artifact that is the result of a process step. See <i>deliverable</i> .
package	pakett	A general purpose mechanism for organizing elements into groups. Packages may be nested within other packages.
parameter	parameeter	The specification of a variable that can be changed, passed, or returned. A parameter may include a name, type, and direction. Parameters are used for operations, messages, and events. Synonyms: <i>formal parameter</i> . Contrast: <i>argument</i> .
parameterized element	parameetritega element	The descriptor for a class with one or more unbound parameters. Synonym: <i>template</i> .
parent	ema	In a <i>generalization</i> relationship, the generalization of another element, the child. See: <i>subclass</i> , <i>subtype</i> . Contrast: <i>child</i> .
participates	osaleb	The connection of a model element to a relationship or to a reified relationship. For example, a class participates in an association, an actor participates in a use case.

partition	sektsoon	1. <i>activity graphs</i> : A portion of an activity graphs that organizes the responsibilities for actions. See: <i>swimlane</i> . 2. <i>architecture</i> : A subset of classifiers or packages at the same level of abstraction. A partition represents a vertical slice through an architecture, whereas a layer represents a horizontal slice. Contrast: <i>layer</i> .
pattern	mall	A scheme for describing design fragments or collections of class templates so that they can be configured and reused.
persistent object	püsiv objekt	An object that exists after the process or thread that created it has ceased to exist.
phase	faas	The time between two major project milestones, during which a well-defined set of objectives is met, artifacts are completed, and decisions are made to move or not move into the next phase.
post-condition	järelingimus	A textual description defining a constraint on the system when a use case has terminated. A constraint that must be true at the completion of an operation.
pre-condition	eelingimus	A textual description defining a constraint on the system when a use case may start. A constraint that must be true when an operation is invoked.
preliminary design review (PDR)	alglahenduse läbivaatus	In the waterfall life-cycle, the major review held when the architectural design is completed (see Guidelines: Project Plan).
primitive type	primitiivtüüp	A pre-defined basic datatype without any substructure, such as an integer or a string.
process	protsess	(1) A thread of control that can logically execute concurrently with other processes, specifically an operating system process. See also: <i>thread</i> . (2) A set of partially ordered steps intended to reach a goal; in software engineering the goal is to build a software product or to enhance an existing one; in process engineering, the goal is to develop or enhance a process model; corresponds to a business use case in business engineering. 1. A heavyweight unit of concurrency and execution in an operating system. Contrast: <i>thread</i> , which includes heavyweight and lightweight processes. If necessary, an implementation distinction can be made using stereotypes. 2. A software development process—the steps and guidelines by which to develop a system. 3. To execute an algorithm or otherwise handle something dynamically.
process view	protsessivaade	An <i>architectural view</i> that describes the concurrent aspect of the system: tasks (processes) and their interactions.
processor	protsessor	A type of node which possesses the capability to run one or more processes. Generally this requires a computational capability, memory, input-output devices, etc. See also: <i>node</i> , <i>process</i> , and <i>device</i> .
product	toode	Software that is the result of development, and some of the associated <i>artifacts</i> (documentation, release medium, training).
product champion	tootejuht	A high-ranking individual who owns the <i>vision</i> of the product and acts as an advocate

product requirements document (PRD)	tootenõuete dokument (PRD)	between development and the <i>customer</i> . A high level description of the product (system), its intended use, and the set of <i>features</i> it provides.
project manager	projekti juht	The worker with overall responsibility for the project. The Project Manager needs to ensure tasks are scheduled, allocated and completed in accordance with project schedules, budgets and quality requirements.
Project Review Authority (PRA)	projekti läbivaatusorgan	The organizational entity to which the Project Manager reports. The PRA is responsible for ensuring that a software project complies with policies, practices and standards (see Concepts: Organizational Context for the Rational Unified Process).
projection property	projektsioon omadus	A mapping from a set to a subset of it. A named value denoting a characteristic of an element. A property has semantic impact. Certain properties are predefined in the UML; others may be user defined. See: <i>tagged value</i> .
protocol	protokoll	A specification of a compatible set of messages used to communicate between <i>capsules</i> . The protocol defines a set of incoming and outgoing messages types (e.g. operations, signals), and optionally a set of sequence diagrams which define the required ordering of messages and a state machine which specifies the abstract behavior that the participants in a protocol must provide.
prototype	prototüüp	A release that is not necessarily subject to <i>change management</i> and <i>configuration control</i> .
pseudo-state	pseudoolek	A vertex in a state machine that has the form of a state, but doesn't behave as a state. Pseudo-states include initial and history vertices.
published model [MOF]	avaldatud mudel	A model which has been frozen, and becomes available for instantiating repositories and for the support in defining other models. A frozen model's model elements cannot be changed.
qualifier	kvalifikaator	An association attribute or tuple of attributes whose values partition the set of objects related to an object across an association.
quality assurance (QA)	kvaliteedi tagamine	The function of Quality Assurance is the responsibility of (reports to) the Project Manager and is responsible for ensuring that project standards are correctly and verifiably followed by all project staff.
race condition	trügimine	A condition which occurs when two or more independent tasks may simultaneously access and modify the same state information. This condition can lead to inconsistent behavior of the system and is a fundamental issue in concurrent system design.
rank	kaalukus	An attribute of a <i>use case</i> or <i>scenario</i> that describes its impact on the <i>architecture</i> , or its importance for a <i>release</i> .
rationale	põhjendus	A statement, or explanation of the reasons for a choice
receive [a message]	vastu võtma	The handling of a stimulus passed from a sender instance. See: <i>sender</i> , <i>receiver</i> .
receiver [object]	vastuvõtja	The object handling a stimulus passed from a sender object. Contrast: <i>sender</i> .

reception	vastuvõtt	A declaration that a classifier is prepared to react to the receipt of a signal.
reference	viide	1. A denotation of a model element. 2. A named slot within a classifier that facilitates navigation to other classifiers. Synonym: <i>pointer</i> .
refinement	täpsustus	A relationship that represents a fuller specification of something that has already been specified at a certain level of detail. For example, a design class is a refinement of an analysis class.
relationship	seos	A semantic connection among model elements. Examples of relationships include <i>associations</i> and <i>generalizations</i> .
release	redaktsioon	A subset of the end-product that is the object of evaluation at a major milestone. See: <i>prototype</i> , <i>baseline</i> .
release manager	redaktsioonijuht	A release manager is responsible for ensuring that all software assets are controlled and configurable into internal and external <i>releases</i> as required.
report	aruanne	An automatically generated description, describing one or several <i>artifacts</i> . A report is not an artifact in itself. A report is in most cases a transitory product of the development process, and a vehicle to communicate certain aspects of the evolving system; it is a snapshot description of artifacts that are not documents themselves.
repository	hoidla	A storage place for object models, interfaces, and implementations.
requirement	nõue	A requirement describes a condition or capability to which a system must conform; either derived directly from user needs, or stated in a contract, standard, specification, or other formally imposed document. See: Concept: Requirements A desired feature, property, or behavior of a system.
requirement attribute	nõude atribuut	Information associated with a particular requirement providing a link between the requirement and other project elements - e.g., priorities, schedules, status, design elements, resources, costs, hazards.
requirements	nõuded	A <i>core process workflow</i> in the software-engineering process, whose purpose is to define what the system should do. The most significant activities are to develop a vision, a use-case model and software requirements specifications.
requirements management	nõudehaldus	A systematic approach to eliciting, organizing and documenting the requirements of the system, and establishing and maintaining agreement between the customer and the project team on the changing requirements of the system. See: Concept: Requirements Management.
requirements tracing	nõudejälitus	The linking of a <i>requirement</i> to other requirements and to other associated project elements.
requirement type	nõude tüüp	A categorization of requirements (e.g., stakeholder need, feature, use case, supplementary requirement, test requirement, documentation requirement, hardware

		requirement, software requirement, etc.) based on common characteristics and attributes. See: Concept: Requirement Types
responsibility	kohustus	A contract or obligation of a classifier.
result	tulem	Synonym of output. See also <i>deliverable</i> .
review	läbivaatus	A review is a group activity carried out to discover potential defects and to assess the quality of a set of <i>artifacts</i> .
reuse	taaskasutus	Further use or repeated use of an <i>artifact</i> . The use of a pre-existing artifact.
risk	risk	An ongoing or upcoming concern that has a significant probability of adversely affecting the success of major milestones.
role	roll	The behavior of a design element participating in a particular context (e.g. use-case realization). See also: <i>analysis class</i> . The named specific behavior of an entity participating in a particular context. A role may be static (e.g., an association end) or dynamic (e.g., a collaboration role).
run time	käitusfaas	The period of time during which a computer program executes. Contrast: <i>modeling time</i> .
scenario	stsenaarium	A described <i>use-case instance</i> , a subset of a <i>use case</i> . A specific sequence of actions that illustrates behaviors. A scenario may be used to illustrate an interaction or the execution of a use case instance. See: <i>interaction</i> .
scope management	ulatus haldus	The process of prioritizing and determining the set of requirements that can be implemented in a particular release cycle, based on the resources and time available. This process continues throughout the lifecycle of the project as changes occur. See also: <i>change management</i> .
schema [MOF]	komplekt	In the context of the MOF, a schema is analogous to a <i>package</i> which is a container of <i>model elements</i> . Schema corresponds to an MOF package. Contrast: <i>metamodel</i> , package corresponds to an MOF package.
semantic variation point	semantilise vabaduse punkt	A point of variation in the semantics of a <i>metamodel</i> . It provides an intentional degree of freedom for the interpretation of the metamodel semantics.
send [a message]	saatma	The passing of a stimulus from a sender instance to a receiver instance. See: <i>sender</i> , <i>receiver</i> .
sender [object]	saatja	The object passing a stimulus to a receiver object. Contrast: <i>receiver</i> .
sequence diagram	järgnevusskeem	A diagram that shows object interactions arranged in time sequence. In particular, it shows the objects participating in the interaction and the sequence of messages exchanged. Unlike a collaboration diagram, a sequence diagram includes time sequences but does not include object relationships. A sequence diagram can exist in a generic form (describes all possible <i>scenarios</i>) and in an instance form (describes one actual scenario). Sequence diagrams and collaboration diagrams express similar information, but show it in different ways. See: <i>collaboration diagram</i> .
signal	signaal	The specification of an asynchronous stimulus

signature	signatuur	communicated between instances. Signals may have parameters. The name and parameters of a behavioral feature. A signature may include an optional returned parameter.	
single inheritance	ainupärilus	A semantic variation of <i>generalization</i> in which a <i>type</i> may have only one <i>supertype</i> . Synonym: <i>multiple inheritance</i> [OMA]. Contrast: <i>multiple inheritance</i> .	
single valued [MOF]	üheväärtuseline	A model element with <i>multiplicity</i> defined is single valued when its Multiplicity Type::upper attribute is set to one. The term single-valued does not pertain to the number of values held by an attribute, parameter, etc., at any point in time, since a single-valued attribute (for instance, with a multiplicity lower bound of zero) may have no value. Contrast: <i>multi-valued</i> .	
software architecture	tarkvara arhitektuur	Software architecture encompasses: (1) the significant decisions about the organization of a software system, (2) the selection of the structural elements and their interfaces by which the system is composed together with their behavior as specified in the collaboration among those elements, (3) the composition of the structural and behavioral elements into progressively larger subsystems, (4) the architectural style that guides this organization, these elements and their interfaces, their collaborations, and their composition. Software architecture is not only concerned with structure and behavior, but also with usage, functionality, performance, resilience, reuse, comprehensibility, economic and technology constraints and tradeoffs, and aesthetic concerns.	
Software Engineering Process Authority (SEPA)	tarkvaratehniline protsessiorgan	The organizational entity with responsibility for process definition, assessment and improvement (see Concepts: Organizational Context for the Rational Unified Process).	
software requirement	tarkvaranõue	A specification of an externally observable behavior of the system, (e.g., inputs to the system, outputs from the system, functions of the system, attributes of the system, or attributes of the system environment).	
software requirements specifications (SRS)	terkvaranõuete spetsifikatsioon	A set of requirements which completely defines the external behavior of the system to be built. (sometimes called a functional specification)	
software specification review (SSR)	tarkvaraspetsifikatsiooni läbivaatus	In the waterfall life-cycle, the major review held when the software requirements specification is complete (see Guidelines: Project Plan).	
specification	spetsifikatsioon	A declarative description of what something is or does. Contrast: <i>implementation</i> .	
stakeholder	osanimik	An individual who is materially affected by the outcome of the system.	JOKA: asjast huvitatatu. "Osanimik jätab mulje, justkui oleks kah pappi sisse pannud juba, aga ei pruugi. Stakeholder

võib olla ka potentsiaalne tulevane kasutaja, kes pole veel millegi eest maksnud, aga kelle arvamust kuulda võetakse.

stakeholder need	osaniku tarve	The business or operational problem (opportunity) that must be fulfilled in order to justify purchase or use.
stakeholder request	osaniku taotlus	A request of any type (e.g., <i>Change Request</i> , <i>enhancement request</i> , request for a requirement change, <i>defect</i>) from a <i>stakeholder</i> .
state	olek	A condition or situation during the life of an object during which it satisfies some condition, performs some activity, or waits for some event. Contrast: <i>state</i> [OMA].
statechart diagram	olekuskeem	A diagram that shows a state machine. See: <i>state machine</i> .
state machine	olekumasin	A state machine specifies the behavior of a <i>model element</i> , defining its response to events and the life cycle of the object. A behavior that specifies the sequences of <i>states</i> that an object or an interaction goes through during its life in response to events, together with its responses and actions.
static artifact	staatiline tehis	An artifact that is used, but not changed, by a process.
static classification	staatiline liigitus	A semantic variation of <i>generalization</i> in which an object may not change type or may not change role. Contrast: <i>dynamic classification</i> .
stereotype	stereotüüp	A meta-classification of an element. Stereotypes have semantic implications which can be specified for every specific stereotype value. See UML Stereotypes in the Rational Unified Process for information on the pre-defined stereotypes in use in the Rational Unified Process. A new type of modeling element that extends the semantics of the metamodel. Stereotypes must be based on certain existing types or classes in the metamodel. Stereotypes may extend the semantics, but not the structure of pre-existing types and classes. Certain stereotypes are predefined in the UML, others may be user defined.
stimulus	stiimul	The passing of information from one instance to another, such as raising a <i>signal</i> or invoking an <i>operation</i> . The receipt of a signal is normally considered an <i>event</i> . See: <i>message</i> .
string	string	A sequence of text characters. The details of string representation depend on implementation, and may include character sets that support international characters and graphics.
structural feature	struktuurne erisus	A static feature of a <i>model element</i> , such as an <i>attribute</i> .
structural model aspect	struktuurne mudeliaspekt	A model aspect that emphasizes the structure of the objects in a system, including their <i>types</i> , <i>classes</i> , <i>relationships</i> , <i>attributes</i> , and <i>operations</i> .

stub	makett	A component containing functionality for testing purposes. A stub is either a pure "dummy", just returning some predefined values, or it is "simulating" a more complex behavior.
subactivity state	alamtegevusolek	A <i>state</i> in an <i>activity graph</i> that represents the execution of a non-atomic sequence of steps that has some duration.
subclass	alamklass	In a generalization relationship, the specialization of another class; the superclass. See: <i>generalization</i> . Contrast: <i>superclass</i> .
submachine state	alammasinaolek	A <i>state</i> in a <i>state machine</i> which is equivalent to a <i>composite state</i> but its contents is described by another state machine.
substate	osaolek	A state that is part of a <i>composite state</i> . See: <i>concurrent substate</i> , <i>disjoint substate</i> .
subsystem	alamsüsteem	A <i>model element</i> which has the semantics of a <i>package</i> , such that it can contain other model elements, and a <i>class</i> , such that it has behavior. (The behavior of the subsystem is provided by classes or other subsystems it contains). A subsystem realizes one or more interfaces, which define the behavior it can perform. A subsystem is a grouping of model elements, of which some constitute a specification of the behavior offered by the other contained model elements. See <i>package</i> . See: <i>system</i> .
subtype	alamtüüp	In a generalization relationship, the specialization of another type; the supertype. See: <i>generalization</i> . Contrast: <i>supertype</i> .
superclass	ülaklass	In a generalization relationship, the generalization of another class; the subclass. See: <i>generalization</i> . Contrast: <i>subclass</i> .
supertype	ülatüüp	In a generalization relationship, the generalization of another type; the subtype. See: <i>generalization</i> . Contrast: <i>subtype</i> .
supplier	tarnija	A classifier that provides services that can be invoked by others. Contrast: <i>client</i> .
swimlane	rada	A partition on a <i>activity diagram</i> for organizing the responsibilities for actions. Swimlanes typically correspond to organizational units in a business model. See: <i>partition</i> .
synch state	sünkroolek	A vertex in a <i>state machine</i> used for synchronizing the concurrent regions of a state machine.
synchronous action	sünkroonne toiming	A request where the sending object pauses to wait for results. Contrast: <i>asynchronous action</i> .
system	süsteem	As an instance, an executable configuration of a software application or software application family; the execution is done on a hardware platform. As a class, a particular software application or software application family that can be configured and installed on a hardware platform. In a general sense, an arbitrary system instance. 1. A collection of connected units that are organized to accomplish a specific purpose. A system can be described by one or more models, possibly from different viewpoints. Synonym: physical system. 2. A top-level subsystem.

system requirements review (SRR)	süsteeminõuete läbivaatus	In the waterfall life-cycle, the name of the major review held when the system specification is completed (see Guidelines: Project Plan).
tagged value	sildiga väärtus	The explicit definition of a property as a name-value pair. In a tagged value, the name is referred as the tag. Certain tags are predefined in the UML; others may be user defined. Tagged values are one of three extensibility mechanisms in UML. See: <i>constraint, stereotype</i> .
target (for test) task	testredaktsioon tegum	A build that is an object for testing. See: <i>build</i> . See: <i>operating system process, process</i> and <i>thread</i> .
team leader	tiimijuht	The team leader is the interface between project management and developers. The team leader is responsible for ensuring that a task is allocated and monitored to completion. The team leader is responsible for ensuring that development staff follow project standards, and adhere to project schedules.
technical authority	tehniline organ	The project's technical authority has the authority and technical expertise to arbitrate on if, and how, a change request is to be implemented. The technical authority defines change tasks, and estimates the effort of engineering the work tasks (corresponding to a <i>change request</i>).
template	tehisemall	A pre-defined structure for an <i>artifact</i> . Synonym: <i>parameterized element</i> .
test	test	A <i>core process workflow</i> in the software-engineering process whose purpose is to integrate and test the system.
test case	testjuhtum	A set of test inputs, execution conditions, and expected results developed for a particular objective, such as to exercise a particular program path or to verify compliance with a specific <i>requirement</i> .
test coverage	testi katvus	The degree to which a given test or set of tests addresses all specified test cases for a given <i>system</i> or <i>component</i> .
test driver	testidraiver	A software module or application used to invoke a test item and, often, provide test inputs (data), control and monitor execution, and report test results. A test driver automates the execution of test procedures.
test item	testredaktsioon	A build which is an object of testing. See: <i>build</i> .
test procedure	testimisprotseduur	A test procedure is a set of detailed instructions for the set-up, execution, and evaluation of results for a given <i>test case</i> .
thread	lõim	An independent computation executing within an the execution environment and address space defined by an enclosing operating system process. Also sometimes called a 'lightweight process'.
thread [of control]	käsulõim	A single path of execution through a program, a dynamic model, or some other representation of control flow. Also, a stereotype for the implementation of an active object as lightweight process. See <i>process</i> .
time	hetk	A value representing an absolute or relative moment in time.

time event	ajasündmus	An event that denotes the time elapsed since the current state was entered. See: <i>event</i> .	
time expression	ajaavaldis	An expression that resolves to an absolute or relative value of time.	
timing mark	ajamärgis	A denotation for the time at which an event or message occurs. Timing marks may be used in constraints.	
tool mentor	instrumentaaljuh	A description which provides practical guidance on how to perform specific process activities or steps using a specific software tool.	
traceability	jälitatus	The ability to trace a project element to other related project elements, especially those related to <i>requirements</i> .	
trace	jälg	A dependency that indicates a historical or process relationship between two elements that represent the same concept without specific rules for deriving one from the other.	
transient object	ajutine objekt	An object that exists only during the execution of the process or thread that created it.	
transition	siire	The fourth <i>phase</i> of the process in which the software is turned over to the user community. A relationship between two <i>states</i> indicating that an object in the first state will perform certain specified actions and enter the second state when a specified event occurs and specified conditions are satisfied. On such a change of state, the transition is said to <i>fire</i> .	
type	tüüp	Description of a set of entities which share common characteristics, relations, attributes, and semantics. A stereotype of class that is used to specify a domain of instances (objects) together with the operations applicable to the objects. A type may not contain any methods. See: <i>class</i> , <i>instance</i> . Contrast: <i>interface</i> .	
type expression	tüübiavaldis	An expression that evaluates to a reference to one or more <i>types</i> .	
UML	UML	Unified Modeling Language [UML98]. In the Rational Unified Process Glossary, definitions from the Unified Modeling Language are indicated by the symbol:	
uninterpreted	tõlgenduseta	A placeholder for a type or types whose implementation is not specified by the UML. Every uninterpreted value has a corresponding string representation. See: <i>any</i> [CORBA].	
usage	kasutus	A dependency in which one element (the <i>client</i>) requires the presence of another element (the <i>supplier</i>) for its correct functioning or implementation.	
use case (class)	kasutusklass	A use case defines a set of <i>use-case instances</i> , where each instance is a sequence of actions a system performs that yields an observable result of value to a particular actor. A use-case class contains all main, alternate flows of events related to producing the 'observable result of value'. Technically, a use-case is a class whose instances are <i>scenarios</i> . The specification of a sequence of actions, including variants, that a system (or other entity) can perform, interacting with <i>actors</i> of the system. See: <i>use-case instances</i> .	JOKA: kasutusjuhtum. "Klass" on kuidagi liiga tehniline, kuna sellest terminist (RUP'i arvates) peaks ka klient aru saama. ARNE: sekundeerin jokale. Sama ka ülejäänud UC terminite puhul
use-case diagram	kasutusklassiskeem	A diagram that shows the relationships among actors and <i>use cases</i> within a system.	

use-case instance	kasutusklassi isend	A sequence of actions performed by a system that yields an observable result of value to a particular actor. The performance of a sequence of actions being specified in a <i>use case</i> . An instance of a use case. See: <i>use-case class</i> .
use-case model	kasutusklassimudel	A model that describes a system's functional <i>requirements</i> in terms of <i>use cases</i> .
use-case package	kasutusklassipakett	A use-case package is a collection of use cases, actors, relationships, diagrams, and other packages; it is used to structure the use-case model by dividing it into smaller parts.
use-case realization	kasutusklassi teostus	A use-case realization describes how a particular use case is realized within the <i>design model</i> , in terms of collaborating objects.
use-case view	kasutusklassivaade	An <i>architectural view</i> that describes how critical use cases are performed in the system, focusing mostly on architecturally significant components (objects, tasks, nodes). In the Unified Process, it is a view of the <i>use-case model</i> .
utility	utiliit	A stereotype that groups global variables and procedures in the form of a class declaration. The utility attributes and operations become global variables and global procedures, respectively. A utility is not a fundamental modeling construct, but a programming convenience.
version	versioon	A variant of some artifact; later versions of an artifact typically expand on earlier versions.
view	vaade	A simplified description (an abstraction) of a model, which is seen from a given perspective or vantage point and omits entities that are not relevant to this perspective. See also <i>architectural view</i> . A projection of a model, which is seen from a given perspective or vantage point and omits entities that are not relevant to this perspective.
view element	vaate element	A view element is a textual and/or graphical projection of a collection of <i>model elements</i> .
view projection	vaate projektsioon	A projection of <i>model elements</i> onto <i>view elements</i> . A view projection provides a location and a style for each view element.
visibility	nähtavus	An enumeration whose value (public, protected, or private) denotes how the <i>model element</i> to which it refers may be seen outside its enclosing <i>namespace</i> .
vision	nägemus	The user's or <i>customer's</i> view of the product to be developed, specified at the level of key <i>stakeholder needs</i> and <i>features</i> of the system.
value	väärtus	An element of a type domain.
vertex	tipp	A source or a target for a transition in a state machine. A vertex can be either a state or a pseudo-state. See: <i>state</i> , <i>pseudo-state</i> .
work guideline	tööjuhised	A description which provides practical guidance on how to perform an activity or set of activities. It usually considers techniques which are useful during the activity.
worker	töötaja	A definition of the behavior and responsibilities of an individual, or a set of individuals working together as a team, within the context of a software engineering

workflow	töövoog	organization. The worker represents a <i>role</i> played by individuals on a project, and defines how they carry out work.
workflow detail	töövoolõik	The sequence of activities performed in a business that produces a result of observable value to an individual actor of the business. A grouping of activities which are performed in close collaboration to accomplish some result. The activities are typically performed either in parallel or iteratively, with the output from one activity serving as the input to another activity. Workflow details are used to group activities to provide a higher level of abstraction and to improve the comprehensibility of workflows.